

Statement of Verification

BREG EN EPD No.: 000238
ECO EPD Ref. No. 00000838

Issue 1

This is to verify that the

Environmental Product Declaration

provided by:

Amtico International



is in accordance with the requirements of:

EN 15804:2012+A1:2013

and

BRE Global Scheme Document SD207

This declaration is for:

Amtico Access Luxury Vinyl Floor Tiles

Company Address

Amtico International
Kingfield Road
Coventry
UK
CV6 5AA




Signed for BRE Global Ltd

Laura Crition
Operator

22 February 2019
Date of this Issue

22 February 2019
Date of First Issue

21 February 2024
Expiry Date



This Statement of Verification is issued subject to terms and conditions (for details visit www.greenbooklive.com/terms).

To check the validity of this statement of verification please, visit www.greenbooklive.com/check or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX.
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: Enquiries@breglobal.com



Environmental Product Declaration

EPD Number: 000238

General Information

EPD Programme Operator	Applicable Product Category Rules
BRE Global Watford, Herts WD25 9XX United Kingdom	BRE Environmental Profiles 2013 Product Category Rules for Type III environmental product declaration of construction products to EN 15804:2012+A1:2013
Commissioner of LCA study	LCA consultant/Tool
Amtico International Kingfield Road, Coventry UK CV6 5AA	BRE/LINA
Declared/Functional Unit	Applicability/Coverage
1m ² of Amtico Access Luxury Vinyl Floor Tiles	Product Average.
EPD Type	Background database
Cradle to Gate with options	ecoinvent
Demonstration of Verification	
CEN standard EN 15804 serves as the core PCR ^a	
Independent verification of the declaration and data according to EN ISO 14025:2010 <input type="checkbox"/> Internal <input checked="" type="checkbox"/> External	
(Where appropriate ^b)Third party verifier: Nigel Jones	
<small>a: Product category rules b: Optional for business-to-business communication; mandatory for business-to-consumer communication (see EN ISO 14025:2010, 9.4)</small>	
Comparability	
Environmental product declarations from different programmes may not be comparable if not compliant with EN 15804:2012+A1:2013. Comparability is further dependent on the specific product category rules, system boundaries and allocations, and background data sources. See Clause 5.3 of EN 15804:2012+A1:2013 for further guidance	

Information modules covered

Product			Construction		Use stage							End-of-life				Benefits and loads beyond the system boundary
					Related to the building fabric				Related to the building							
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Raw materials supply	Transport	Manufacturing	Transport to site	Construction – Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse, Recovery and/or Recycling potential
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>									

Note: Ticks indicate the Information Modules declared.

Manufacturing site(s)

Make under contract in the Republic of South Korea

Construction Product

Product Description

Amtico Access is a design-led, loose lay vinyl tile collection, consisting of 43 products: 18 Wood, 10 Stone and 15 Abstract designs.

Amtico Access is a 5.0 mm product with a 0.55 mm wear layer and is classified as per EN ISO 10874 for use in the following areas.

1. Class 23, Heavy Domestic
2. Class 33, Heavy Commercial
3. Class 42, General Light Industrial

Amtico Access products are recommended for use over properly prepared concrete, suspended wood, metal and other suitable substrates using Amtico Tackifier. Amtico Access products should not be installed until the sub-floor preparation and the work of all other trades has been completed.

Amtico Access products can be used with radiant heating systems, however the product must be fully bonded and the surface temperature of the subfloor must not exceed 27°C (81°F).

Amtico Access products are not intended for outside use.

Details of Amtico Access Cleaning and Maintenance can be found at,

<https://www.amtico.com/media/1513257/amtico-access-maintenance-guidelines-acc-ma-300916-01-gb.pdf>

Technical Information

Property	Value, Unit
Usage Classification (EN ISO 10874)	23,33,42
Manufacturing Standard (EN 10582)	Pass
Total Thickness (EN ISO 24346)	5.0mm
Wear Layer Thickness (EN ISO 24340)	0.55mm
Weight (EN ISO 23997)	7800 g/m ²
Abrasion Resistance (EN 10582)	Type 1
Residual Indentation (EN ISO24343-1)	≤0.1mm
Dimensional Stability (EN ISO23999)	≤0.5%
Dimensional Stability, Curling (EN ISO 23999)	≤1mm
Flexibility (EN ISO 24344 Method A)	Pass
Slip Resistance (DIN 51130)	R10
Slip Resistance (EN13893)	Class DS
Chemical Resistance (EN ISO 26987)	Excellent
Light Stability (EN ISO 105-B02)	≥6
Flammability /Smoke Emissions (EN 13501-1)	B _{fl} s1
Castor Chair Resistance (EN ISO 4918) (Type W)	Pass
Impact Sound Reduction (EN ISO 717-2)	9dB
Electrostatic Performance (EN1815)	≤ 2 kV
Emissions (France - Emissions dans l'air interieur)	A+
Eurofins Indoor Air Comfort Gold	IACG-352-03-07-2018
Amtico First Technical Data Sheet is available on the Amtico website. https://www.amtico.com/commercial/technical/docs/first-collection	

Main Product Contents

Material/Chemical Input	%
Urethane Lacquer	<0.5
Polyvinyl chloride	40
Plasticisers	15
Filler	44
Stabilisers & Pigments	<1.0


Manufacturing Process

The product is constructed by the thermal lamination of the wear layer, print film and backing plies. The wear layer and backing plies are all manufactured as follows,

1. Required ply raw materials are initially blended.
2. The ply blend is then heated and calendered on a mill to produce a ply of the required thickness.
3. The plies required to form the end product, along with the print film, are thermally laminated together under pressure, to form the final product.
4. The product is then coated with polyurethane, before being cut to size, boxed and dispatched to the customer.

Cutting waste is recycled back into the product

Process flow diagram



Construction Installation

Amtico Access should be bonded with a suitably low emissions tackifier to an appropriately prepared subfloor as detailed in BS8302. Full details on installation can be found at:

<https://www.amtico.com/media/1513258/amtico-access-installation-guidelines-acc-in-300916-01-gb.pdf>

Installation off-cuts can be disposed of via recycling such as AgPR, energy recovery schemes or landfilled. Wherever possible it is recommended that products should always be recycled.

Use Information

Emissions

Amtico Access adheres to the emission requirements of Indoor Air Comfort Gold, German AgBB/DIBt, Belgium, and is rated as A+ in the French "Emissions dans l'air interieur" scheme.

End of Life

At the end of the product's life, the flooring is lifted off the subfloor and disposed of by landfill or Incineration/energy recovery.

It is assumed that 80% of the product will go to landfill, with the remaining 20% being recycled or used in energy recovery schemes. The distance travelled from the demolition site to a disposal site will be no more than 200km.

Life Cycle Assessment Calculation Rules

Declared / Functional unit description

1m² Amtico Access Luxury Vinyl Floor Tiles

System boundary

Modules A1-A3: Includes raw materials, energy, water and transport processes required to make the product up to the factory gate, as well as production, packaging and general site waste.

Module A4: Transport from factory gate to the UK and then to the installation site. Distance was calculated as an average based on product sales across UK, Europe, Middle and Far East.

Module A5: Floor installation, including adhesive and disposal of off-cuts and packaging.

Module B2: Electricity, water, cleaning products required to clean and maintain the product for one year.

Module C1: The amount of electricity required to remove a floor.

Module C2: Transportation of removed flooring to landfill or energy recovery site. Assumed distance is 200km.

Module C3: Waste processing of flooring waste.

Module C4: Disposal

Data sources, quality and allocation

In addition to Amtico Access, other LVT products are also manufactured at the same production site. Calculations were performed to enable allocation of total site energy use, water and waste to the Amtico Access production. Allocation procedures were by physical allocation and are according to EN 15804 and are based on the ISO14044 guidance

Transportation distances were calculated for Amtico Access, based on the percentage of total square meters supplied to a distribution centre or sales region and the distance to the distribution centre or sales region.

The LCA was calculated using BRE LINA V2.0.8 with Ecoinvent

Cut-off criteria

1. Transport distances to site were not calculated for Sales Business Units with <1% of product sales.
2. The product life was based on the commercial 10 years warranty.

LCA Results

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing environmental impacts			GWP	ODP	AP	EP	POCP	ADPE	ADPF
			kg CO ₂ equiv.	kg CFC 11 equiv.	kg SO ₂ equiv.	kg (PO ₄) ³⁻ equiv.	kg C ₂ H ₄ equiv.	kg Sb equiv.	MJ, net calorific value.
Product stage	Raw material supply	A1	9.64e+0	4.04e-7	3.53e-2	1.18e-2	9.64 e-3	5.48e-5	2.22e+2
	Transport	A2	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Manufacturing	A3	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Total (of product stage)	A1-3	9.64e+0	4.04e-7	3.53e-2	1.18e-2	9.64 e-3	5.48e-5	2.22e+2
Construction process stage	Transport	A4	4.10e+0	9.71e-8	4.72e-2	6.67e-3	4.46e-3	6.91e-6	6.03e+1
	Construction	A5	9.23e--1	1.10e-	5.63e-3	1.52e-3	1.03e-3	4.83e-6	2.10e+1
Use stage	Use	B1	MND	MND	MND	MND	MND	MND	MND
	Maintenance	B2	1.10e+1	7.92e-7	6.09e-2	1.66e-2	4.34e-3	2.05e-5	1.89e+2
	Repair	B3	MND	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND	MND
End of life	Deconstruction, demolition	C1	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Transport	C2	2.61e-1	4.80e-8	8.72e-4	2.30e-4	1.52e-4	6.87e-7	3.94e+0
	Waste processing	C3	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Disposal	C4	4.00e-1	1.71e-8	1.27e-3	2.36e-2	1.39e-4	9.34e-8	1.59e+0
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	MND	MND	MND	MND	MND	MND	MND

GWP = Global Warming Potential;
 ODP = Ozone Depletion Potential;
 AP = Acidification Potential for Soil and Water;
 EP = Eutrophication Potential;

POCP = Formation potential of tropospheric Ozone;
 ADPE = Abiotic Depletion Potential – Elements;
 ADPF = Abiotic Depletion Potential – Fossil Fuels;

LCA Results (continued)

Parameters describing resource use, primary energy			PERE	PERM	PERT	PENRE	PENRM	PENRT
			MJ	MJ	MJ	MJ	MJ	MJ
Product stage	Raw material supply	A1	1.08e+1	4.22e-4	1.08e+1	2.57e+2	0.00e+0	2.57e+2
	Transport	A2	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Manufacturing	A3	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Total (of product stage)	A1-3	1.08e+1	4.22e-4	1.08e+1	2.57e+2	0.00e+0	2.57e+2
Construction process stage	Transport	A4	1.26e+0	4.37e-6	1.26e+0	6.09e+1	0.00e+0	6.09e+1
	Construction	A5	1.68e+0	2.36e-5	1.68e+0	2.30e+1	0.00e+0	2.30e+1
Use stage	Use	B1	MND	MND	MND	MND	MND	MND
	Maintenance	B2	1.41e+1	3.56e-5	1.41e+1	2.40e+2	0.00e+0	2.40e+2
	Repair	B3	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND
End of life	Deconstruction, demolition	C1	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Transport	C2	5.23e-2	1.95e-7	5.23e-2	3.91e+0	0.00e+0	3.91e+0
	Waste processing	C3	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Disposal	C4	5.09e-2	1.40e-7	5.09e-2	1.61e+0	0.00e+0	1.61e+0
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	MND	MND	MND	MND	MND	MND

PERE = Use of renewable primary energy excluding renewable primary energy used as raw materials;
 PERM = Use of renewable primary energy resources used as raw materials;
 PERT = Total use of renewable primary energy resources;

PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials;
 PENRM = Use of non-renewable primary energy resources used as raw materials;
 PENRT = Total use of non-renewable primary energy resource

LCA Results (continued)

Parameters describing resource use, secondary materials and fuels, use of water						
			SM	RSF	NRSF	FW
			kg	MJ net calorific value	MJ net calorific value	m ³
Product stage	Raw material supply	A1	0.00e+0	0.00e+0	0.00e+0	5.21e-1
	Transport	A2	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Manufacturing	A3	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Total (of product stage)	A1-3	0.00e+0	0.00e+0	0.00e+0	5.21e-1
Construction process stage	Transport	A4	0.00e+0	0.00e+0	0.00e+0	1.49e-2
	Construction	A5	0.00e+0	0.00e+0	0.00e+0	4.40e-2
Use stage	Use	B1	MND	MND	MND	MND
	Maintenance	B2	0.00e+0	0.00e+0	0.00e+0	7.99e-2
	Repair	B3	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND
End of life	Deconstruction, demolition	C1	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Transport	C2	0.00e+0	0.00e+0	0.00e+0	8.54e-4
	Waste processing	C3	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Disposal	C4	0.00e+0	0.00e+0	0.00e+0	1.80e-3
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	MND	MND	MND	MND

SM = Use of secondary material;
RSF = Use of renewable secondary fuels;

NRSF = Use of non-renewable secondary fuels;
FW = Net use of fresh water

LCA Results (continued)

Other environmental information describing waste categories					
			HWD	NHWD	RWD
			kg	kg	kg
Product stage	Raw material supply	A1	2.51e-1	5.32e-1	3.32e-4
	Transport	A2	0.00e+0	0.00e+0	0.00e+0
	Manufacturing	A3	0.00e+0	0.00e+0	0.00e+0
	Total (of product stage)	A1-3	2.51e-1	5.32e-1	3.32e-4
Construction process stage	Transport	A4	3.19e-2	1.57e+0	4.10e-4
	Construction	A5	2.05e-2	1.38e-1	5.65e-5
Use stage	Use	B1	MND	MND	MND
	Maintenance	B2	6.00e-2	4.57e-1	1.15e-3
	Repair	B3	MND	MND	MND
	Replacement	B4	MND	MND	MND
	Refurbishment	B5	MND	MND	MND
	Operational energy use	B6	MND	MND	MND
	Operational water use	B7	MND	MND	MND
End of life	Deconstruction, demolition	C1	0.00e+0	0.00e+0	0.00e+0
	Transport	C2	1.65e-3	1.84e-1	2.72e-5
	Waste processing	C3	0.00e+0	0.00e+0	0.00e+0
	Disposal	C4	1.21e-3	6.25e+0	9.97e-6
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	MND	MND	MND

HWD = Hazardous waste disposed;
 NHWD = Non-hazardous waste disposed;
 RWD = Radioactive waste disposed

LCA Results (continued)

Other environmental information describing output flows – at end of life						
			CRU	MFR	MER	EE
			kg	kg	kg	MJ per energy carrier
Product stage	Raw material supply	A1	0.00e+0	0.00e+0	2.52e-2	0.00e+0
	Transport	A2	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Manufacturing	A3	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Total (of product stage)	A1-3	0.00e+0	0.00e+0	2.52e-2	0.00e+0
Construction process stage	Transport	A4	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Construction	A5	0.00e+0	3.57e-1	3.91e-1	0.00e+0
Use stage	Use	B1	MND	MND	MND	MND
	Maintenance	B2	0.00e+0	0.00e+0	6.24e-2	0.00e+0
	Repair	B3	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND
End of life	Deconstruction, demolition	C1	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Transport	C2	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Waste processing	C3	0.00e+0	0.00e+0	0.00e+0	0.00e+0
	Disposal	C4	0.00e+0	0.00e+0	1.56e+1	0.00e+0
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	MND	MND	MND	MND

CRU = Components for reuse;
MFR = Materials for recycling

MER = Materials for energy recovery;
EE = Exported Energy

Scenarios and additional technical information

Scenarios and additional technical information			
Scenario	Parameter	Units	Results
A4 – Transport to the building site	Products are shipped to Coventry and then distributed in the UK, across Europe, Scandinavia, the Middle and Far East. The average distance transported for each geographical market was calculated by multiplying the distance travelled by the percentage sales volume by square meter. Sales regions where sales were less than 1% were not considered.		
	The sales volumes were those in 2017. The transportation data is taken from Ecoinvent datasets.		
	Worldwide: Ship to UK	Litre of fuel type per distance or vehicle type	303l/km
	Distance:	km	20257
	Capacity utilisation (incl. empty returns)	%	65
	Bulk density of transported productskg/m ³	kg/m ³	1560
	Worldwide: Ship to UK	Diesel / 16-32 tonne Lorry	0.032l/km
	Distance:	km	303
	Capacity utilisation (incl. empty returns)	%	35
	Bulk density of transported productskg/m ³	kg/m ³	1560
	UK Direct Delivery: Diesel/Vehicle	Litre of fuel type per distance or vehicle type	0.32l/km
	Distance	km	60
	Capacity utilisation (Inc. empty return)	%	Not Stated
	Bulk density of transported productskg/m ³	kg/m ³	1560
	Worldwide: Road	Diesel / 16-32 tonne Lorry	0.032l/km
	Distance:	km	974
	Capacity utilisation (incl. empty returns)	%	35
	Bulk density of transported productskg/m ³	kg/m ³	1560
	Worldwide: Ship	Litre of fuel type per distance or vehicle type	303l/km
	Distance:	km	442
	Capacity utilisation (incl. empty returns)	%	65
	Bulk density of transported productskg/m ³	kg/m ³	1560

A5 – Installation in the building	<p>Amtico Access should be bonded with a suitable low emission Tackifier to an appropriately prepared subfloor as detailed in BS8302. Full details on installation can be found at www.amtico.com. Installation off cuts can be disposed of via recycling, used in energy recovery schemes or landfilled. Wherever possible it is recommended that products should always be recycled.</p>		
	% Installation Wastage Rate		5
	Post installation Cleaning	l/m ²	0.02
	Ancillary Materials	Mass per unit area of product installed kg/m ²	0.288
	Material Waste	Installation off cuts mass per unit area of product installed kg/m ²	0.39
	Cardboard Packaging	Mass per unit area of product installed kg/m ²	0.201
	Wood Packaging	Mass per unit area of product installed kg/m ²	0.154
	Shrink Wrap	Mass per unit area of product installed kg/m ²	0.001
B2 – Maintenance	<p>The required recommended cleaning and maintenance regime is dependent on the place of installation and the foot traffic over the floor. High traffic areas will generally require more cleaning and maintenance than low traffic situations. Dry cleaning may be performed with a dust mop or with a vacuum cleaner. Wet cleaning can be performed with a mop, detergent and water. Power cleaning is also a possibility with scrubber driers etc. The calculations are assumed for 1m² per year.</p>		
	52 Powered Cleaning operations a year, 1.5kW machine	kWh/m ²	0.27
	52 Wet Cleans per year (Water use)	l/yr./m ²	3.224
	Detergent usage	kg/yr./m ²	0.0416
Reference service life	<p>Amtico International (hereinafter referred to as the Company) hereby guarantees in the event of the Amtico Access flooring supplied to the original purchaser under this agreement, requiring replacement due to 'Wear-out' from normal foot traffic, within ten years from the date of purchase, the floor will be repaired or replaced with the same or similar material free of charge. 'Wear-out' means the removal of the pattern and colour from the Amtico Access floor caused by the removal of the protective wear layer.</p>		
	Commercial Product Warranty	Years	10
	<p>Commercial and residential warranties can be found on the Amtico website https://www.amtico.com/commercial/technical/docs/access/</p>		
C1 to C4 End of life,	Description of scenario		
C1	At the end of the product's life, the flooring is lifted from the subfloor and disposed of by landfill or Incineration/energy recovery.		
C2	It is assumed that 80% of the dismantled flooring goes to landfill and the remaining 20% is incinerated for energy recovery or recycled. The disposal sites are within 200km of the demolition site.		
C3	The floor is lifted from the installation and is then processed as follows, Landfill 80%. No further processing required. Incineration/energy recovery 20%. No further processing required		
C4	Final disposal		

	Polyvinyl chloride Waste to Energy recovery	kg	1.56
	Polyvinyl chloride Waste to landfill	kg	6.24

Summary, comments and additional information

Product Brochures

Amtico Access brochure is available at
<https://www.amtico.com/commercial/brochures/>

Technical Product Information

AmticoAccess Technical Data Sheet and Declaration of Performance, are available on the Amtico website.
<https://www.amtico.com/commercial/technical/docs/access/>

Technical Standards

Copies of the test standards quoted in the Technical Data Sheets are available from the British Standards Institute website.
<https://shop.bsigroup.com/>

Warranties

Commercial warranty can be found on the Amtico website
<https://www.amtico.com/commercial/technical/docs/access/>

Installation and Aftercare

Installation, adhesives and aftercare instructions are available on the Amtico Website at
<https://www.amtico.com/commercial/technical/docs/access/>

Example of Amtico Access

Fig1 Image of product



Amtico Logo

amtico
A MANNINGTON COMPANY

References

BSI. Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products. BS EN 15804:2012+A1:2013. London, BSI, 2013.

BSI. Environmental labels and declarations – Type III Environmental declarations – Principles and procedures. BS EN ISO 14025:2010 (exactly identical to ISO 14025:2006). London, BSI, 2010.

BSI. Environmental management – Life cycle assessment – Principles and framework. BS EN ISO 14040:2006. London, BSI, 2006.

BSI. Environmental management – Life cycle assessment – requirements and guidelines. BS EN ISO 14044:2006. London, BSI, 2006.