



## DECLARATION OF PERFORMANCE

No. 001\_CasalgrPad

- Unique identification code of the product type:  
**Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5 \%$**
- Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5 \%$**
- Intended use(s)  
**For internal and external walls and floorings**
- Name or registered trade mark, and contact address of the manufacturer  
**Casalgrande Padana SpA, Via Statale 467,73 Casalgrande (RE)**
- N.A.
- System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
- Name and identification number of notified laboratory, if relevant N.A.  
Task(s) carried out N.A.  
AVCP system N.A.  
Document issued and date of issue N.A.
- N.A.
- Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 <sub>FL</sub> /A1	Based on the decision 96/603/CE and its changes
Release of dangerous substance, for:		EN 14411:2012
- Cadmium*	NPD	
- Lead*	NPD	
Breaking strength Thickness $\geq 7.5$ mm	> 1 300 N	
Breaking strength Thickness < 7.5 mm	> 700 N	
Slipperiness**	NPD	
Tactility***	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

\* Only necessary in the case of materials that come into contact with foodstuffs or when required by corresponding national statutory regulations  
 \*\* Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information in our catalogue and technical specification.  
 \*\*\* Only for tactile floorings, meaning if requested for blind and visually impaired: as a description of the surface

- The performance of the product identified in point 1 is in conformity with the declared performances in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

ING. GABRIELE BORGHI (TECHNICAL SERVICE)  
Name and function

CASALGRANDE (RE) 01/07/2013  
Place and date of issue

Signature



**Casalgrande Padana SpA,**  
**42013 Via Statale 467,73 Casalgrande (RE)**

**05**

**001\_CasalgrPad**

**EN 14411:2012**  
Dry-pressed ceramic tiles, with water  
absorption  $E_b \leq 0,5\%$ , for internal and external walls and floorings

<b>Reaction to fire</b>	A1 <sub>FL</sub>
<b>Release of dangerous substances, for:</b>	
- Cadmium*	NPD
- Lead*	NPD
<b>Breaking strength</b>	> 1300 N
<b>Slipperiness**, as:</b>	
PTV slider 57, CEN/TS 16165:2011 Annex C	NPD
<b>Durability for:</b>	
- Internal use:	Pass
- External use: freeze-thaw resistance	Pass

\* Only necessary in the case of materials that come into contact with foodstuffs or when required by corresponding national statutory regulations

\*\*Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information in our catalogue and technical specification.