



Acoustix Forest fx

HETEROGENEOUS



Birch Core 3295

W1 1200

L26 180

Oak Core 3285

W1 1200

L26 180

W1 1200

L26 180



Maple Core 3295

W1 1200

L26 180

Walnut Core 3245

W1 1200

L26 180

W1 1200

L26 180



Oak Core 3095

W1 1200

L26 180

Walnut Core 3125

W1 1200

L26 180

W1 1200

L26 180



Walnut Core 3155

W1 1200

L26 180

Oak Core 3225

W1 1200

L26 180

W1 1200

L26 180

W1 1200 in colour and design is a feature of this product. Intended to enhance the realistic appearance of the floor.

W1 1200 in colour and design is a feature of this product. Intended to enhance the realistic appearance of the floor.



Acoustix Forest fx

This wood effect vinyl sheet flooring provides high impact noise reduction for very busy commercial areas.

Polyflor Acoustix Forest fx PUR is suitable for use in residential or commercial buildings where sound insulation is an important feature, for example schools, hospitals and student accommodation.



Geog	ISO 24346 (EN 428)	3.7mm
Wear Layer	ISO 24343 (EN 429)	0.55mm
Roll Size	ISO 24341 (EN 426)	2m x 20m x 40m
Total Weight	ISO 23997 (EN 430)	2550g/m ²
General Performance	ISO 1608 (EN 651)	Conforms
Use Area	ISO 10874 (EN 685)	Conforms
Acoustic Impact Sound Reduction	EN 153 10360-3	19dB
Resistance to Chemicals	EN 423	Excellent chemical resistance
Reaction to Fire	EN 135014	Class Bfl-s1
Abrasion Resistance	EN 455	Group T
Slip Resistance*	EN 13813	Class DS (dry conditions)
Residual Indentation	EN 4286	W1
Dimensional Stability	ISO 23999 (EN 434)	±0.20mm
Flexibility	ISO 24348 (EN 436)	±0.4%
Thermal Resistance	EN 12667	0.057m ² K/W
Static Electrical Property	EN 1815	Classified as antistatic
Light Fastness	ISO 105 B02	Method 3: 16
VOC Emissions	AgBB VOC test	Carpet certified product
Flammability	Flammability	Very low emissions
Response Sourcing	BES 6001	Certified
Environmental Preference	Polyflor Acoustix Forest fx PUR achieves a BREE Global Air rating (EN 428) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag (CA) Rate certified with GreenTag award A - Gold Plus, GreenTag (EN 16004) Environmental Product Declaration (EPD) available on request. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability	
PUR	Polyflor Acoustix Forest fx PUR features a high quality cross-linked polyurethane reinforcement, UV cured to provide a low cost, polished, multi-layered surface for the lifetime of the flooring.	
Hygienic	Polyflor Acoustix Forest fx PUR provides a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved hygiene products. The implementation of an effective cleaning regime is the most important defence against infection.	
For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)1628 762 702 or email tech@polyflor.com .		
*Slip safety flooring with sustainable wet slip resistance: refer to Porosafe ranges.		
The data presented here is correct at the time of printing. For latest information, please visit our website polyflor.com .		
Declaration and shade may vary slightly from the samples shown.		



UK Sales Direct +44 (0)1628 762 702 | Export Sales Direct +44 (0)1628 762 703
Sample Requests +44 (0)1628 762 700 | email info@polyflor.com | www.polyflor.com



June 2024 0719