

Polyclad Pro

WALL CLADDING



White Chalk 4093

wH 4093



Frosted Grey 4094

wH 4094



Biscuit Beige 4092

wH 4092



Blue Shingle 4097

wH 4097



Grey Steel 4095

wH 4095



Dusted Blue 4096

wH 4096













 **100% RECYCLABLE**
25% RECYCLED MATERIAL

wH = wall roll NCS = Natural Colour System LRV = Light Reflectance Value

Polyclad Pro

Tough, durable and low maintenance PVC wall and ceiling cladding, with subtle marblesation. Welded Polyclad Pro PU creates an impervious, continuous surface which offers no sanctuary to dirt and bacteria and will not shed dust. Developed specifically to meet the advanced requirements of today's medical, science and electronics industries. Polyclad Pro PU is suitable for use in cleanrooms, semi-conductor manufacture, precision machinery manufacture, the pharmaceuticals industry, food processing plants and any area where hygiene is important. It is recommended that Polyclad Pro PU is used in conjunction with the Polyflor range of vinyl floorcoverings.



	General Performance	EN ISO2:2007 +A1:2011	Heavy duty wallcoverings
	Total Thickness	EN 428/EN ISO 24346	1.25mm
	Roll Size	EN 426/ISO 24341	1.83m x 30m = 54.9m ²
	Total Weight	EN 430/ISO 23997	1900g/m ²
	Reaction to Fire	EN 135011 AS/NZS 3837 ISO 5660 ASTM E84 CAN/ULC S402.2	Class B-s2-d0 Group 1 NZBC Verification Method C/VM2 Appendix A: Class 5 smoke less than 250m ² /kg NCC Specifications C1.3.0 and A.2.4. Class 1 smoke less than 250m ² /kg Class A FSV + ZS, FDV + S0
	Clean rooms	ASTM F516/68 ISO 14644-1:1999	Class A -non-shedding Class 4
	VOC Emissions	AqBB VOC test	Pass
	Flexibility	EN 435/ISO 24344	Pass
	Resistance to Chemicals	EN 423	Good resistance to dilute acids and alkalis. Chemical resistance charts available on request.
	Light Fastness	ISO 105 B02	(Method 3) -6
Environmentally Preferable Flooring - Polyclad Pro PU is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability .			
	Hygiene	All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.	
	Product suitability	This product is suitable for steam cleaning on a periodic basis. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com . The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com .	

 **100% RECYCLABLE**
25% RECYCLED MATERIAL     

